

AURORA 1500 PL

LIGHT SOURCE

LED quantity	1
Power max	18 W
Total lumen output (3000K CRI>90)	15° - 1393 lm 25° - 1578 lm 40° - 1275 lm
Efficacy lm/W (3000K CRI>90)	15° - 77 lm/W 25° - 88 lm/W 40° - 71 lm/W
LED Temperature	2700K- 3000K - 3000K CRI>90 – 4000K 3000K CRI>90 DIM TO WARM
Average operational life	50.000 hours

OPTIC

Material	Metalized plastic reflector
Available optics	15° - 25° - 40°
Beam direction	Adjustable +/-90°, rotating +/-355°
Flux symmetry	Symmetrical

FIXTURE

Material	Aluminum
Available finishes	Powder coating: 7 - White H - Black W - All white
IP Rate	IP40
Working Temperature	-20° ÷ +40°
Integrated fixing Systems	Applique base for inner connections

ELECTRICAL FEATURES



Driver	Remote
Dimmable	Push, 1-10V, DALI
Connection	In series at 500mA (350 mA – DIM TO WARM version only)
Class	III

MECHANICAL FEATURES




Dimensions (body)	Ø55 x 140 mm
Weight	600 gr
Installation	Wall, ceiling mounting
Cut-out	-
Use	Indoor

ACCESSORIES

Visors	Hex louver (A00732.40)
Filters	-
Box/ Frame	-
Fixing system	-



PHOTOMETRIC DATA

15° Lens – 18W	25° Lens – 18W	40° Lens – 18W																																																																																					
																																																																																							
<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td colspan="4">15°</td> </tr> <tr> <td><u>1.00</u></td><td>0.34</td><td>8551</td><td>5331</td></tr> <tr> <td><u>2.00</u></td><td>0.67</td><td>2138</td><td>1333</td></tr> <tr> <td><u>3.00</u></td><td>1.01</td><td>950</td><td>592</td></tr> <tr> <td><u>4.00</u></td><td>1.35</td><td>534</td><td>333</td></tr> <tr> <td><u>5.00</u></td><td>1.69</td><td>342</td><td>213</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	15°				<u>1.00</u>	0.34	8551	5331	<u>2.00</u>	0.67	2138	1333	<u>3.00</u>	1.01	950	592	<u>4.00</u>	1.35	534	333	<u>5.00</u>	1.69	342	213	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td colspan="4">25°</td> </tr> <tr> <td><u>1.00</u></td><td>0.44</td><td>7370</td><td>4610</td></tr> <tr> <td><u>2.00</u></td><td>0.87</td><td>1843</td><td>1152</td></tr> <tr> <td><u>3.00</u></td><td>1.31</td><td>819</td><td>512</td></tr> <tr> <td><u>4.00</u></td><td>1.75</td><td>461</td><td>288</td></tr> <tr> <td><u>5.00</u></td><td>2.19</td><td>295</td><td>184</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	25°				<u>1.00</u>	0.44	7370	4610	<u>2.00</u>	0.87	1843	1152	<u>3.00</u>	1.31	819	512	<u>4.00</u>	1.75	461	288	<u>5.00</u>	2.19	295	184	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td colspan="4">40°</td> </tr> <tr> <td><u>1.00</u></td><td>0.63</td><td>3768</td><td>2281</td></tr> <tr> <td><u>2.00</u></td><td>1.27</td><td>942</td><td>570</td></tr> <tr> <td><u>3.00</u></td><td>1.90</td><td>419</td><td>253</td></tr> <tr> <td><u>4.00</u></td><td>2.53</td><td>236</td><td>143</td></tr> <tr> <td><u>5.00</u></td><td>3.17</td><td>151</td><td>91</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	40°				<u>1.00</u>	0.63	3768	2281	<u>2.00</u>	1.27	942	570	<u>3.00</u>	1.90	419	253	<u>4.00</u>	2.53	236	143	<u>5.00</u>	3.17	151	91	
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																				
15°																																																																																							
<u>1.00</u>	0.34	8551	5331																																																																																				
<u>2.00</u>	0.67	2138	1333																																																																																				
<u>3.00</u>	1.01	950	592																																																																																				
<u>4.00</u>	1.35	534	333																																																																																				
<u>5.00</u>	1.69	342	213																																																																																				
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																				
25°																																																																																							
<u>1.00</u>	0.44	7370	4610																																																																																				
<u>2.00</u>	0.87	1843	1152																																																																																				
<u>3.00</u>	1.31	819	512																																																																																				
<u>4.00</u>	1.75	461	288																																																																																				
<u>5.00</u>	2.19	295	184																																																																																				
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																				
40°																																																																																							
<u>1.00</u>	0.63	3768	2281																																																																																				
<u>2.00</u>	1.27	942	570																																																																																				
<u>3.00</u>	1.90	419	253																																																																																				
<u>4.00</u>	2.53	236	143																																																																																				
<u>5.00</u>	3.17	151	91																																																																																				
UGR=9	UGR=7	UGR=10																																																																																					

NOTES