


ASTRO 80













-  IP67
-  Class III
-  Incasso a parete, soffitto, pavimento
Wall, ceiling, floor recessed
-  WIPS - Water Infiltration Protection System
-  Carrabile 2000 kg
Drive over up to 2000 kg
-  Cavo in neoprene 100 cm
100 cm neoprene cable
(disponibile lunghezza cavo su misura)
(additional cable length available upon request)
-  Collegare in serie 350mA o 500mA
Connect in series at 350mA or 500mA
-  220 gr
-  Altamente riciclabile
Highly recyclable




Altezza d'installazione contenuta
Adatto a bassi spessori
Tre potenze disponibili

Limited installation height
Suitable for low thicknesses
Three powers available

■ ASTRO 80

	1W 350mA	2W 500mA	3W 350mA	Finiture Finish	Colore LED LED Colour
Lumen 3000K	100lm	150lm	300lm		
 15° Lens			7A0858._ _	<ul style="list-style-type: none">  3 Grigio - Gray  4 Nero - Black  6 Acciaio Inox Stainless Steel AISI 316L 	<ul style="list-style-type: none">  U 2200K  Y 2700K  6 3000K  9 4000K
 30° Lens			760858._ _		
 60° Lens			750858._ _		
 Vetro satinato Frosted glass	710857._ _	710796._ _			
 Lente ellittica Elliptical lens			770858._ _		




ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

350mA CC20-F-350-N
500mA CC20-F-500-N

ACCESSORI
ACCESSORIES



Controcassa
Recessed box
A00658.30

 Ø 74 mm

EXAMPLE CODE COMPOSITION
123456.

LED COLOUR
FINISH