

LIGHT SOURCE

LED quantity	1
Power max	25 W
Total lumen output (3000K)	2575 lm
Efficacy lm/W (3000K)	103 lm/W
LOR (3000K)	74%
CRI	>80 – >90
LED Temperature (K)	2700 K – 3000 K – 3000K CRI>90 – 4000 K
Average operational life	50.000 hours

OPTIC

Material	Glass reflector
Available optics	10°-20°-30°-40°
Beam direction	Adjustable +/-90°, Rotating +/-355°
Flux symmetry	Symmetrical
Accessories	-

LED FIXTURE

Material	Aluminum
Finish	Painted (Black, White, All White)
Available finishes	Black, White, All White
IP Rate	IP40
Working Temperature	-20° ÷ +40°
Accessories	-



ELECTRICAL FEATURES

Driver	Remote
Dimmable	Push, 1-10V,DALI
For emergency lighting	Upon request
Connection in	In series at 700mA
Class	III

MECHANICAL FEATURES

Dimensions (mm)	Ø75 x 150 (cylinder only)
Weight	750 gr
Mounting	Wall, ceiling mounting
Cut-out (mm)	-
Use	Indoor

NOTES



25W

H(m)	D(m)	E _{max} (lx)	E _{av} (lx)
20°			
1.00	0.36	11691	7418
2.00	0.73	2923	1855
3.00	1.09	1299	824
4.00	1.46	731	464
5.00	1.82	468	297