










DGA

## GEMMA Qd 35 IP67







-  IP67
-  Class III
-  Incasto a parete, soffitto, pavimento  
Wall, ceiling, floor recessed
-  WIPS - Water Infiltration Protection System
-  Carrabile 2000 kg  
Drive over up to 2000 kg
-  Cavo in neoprene 100 cm  
100 cm neoprene cable  
(disponibile lunghezza cavo su misura)  
(additional cable length available upon request)
-  Collegare in serie 350mA o 500mA  
Connect in series at 350mA or 500mA
-  120 gr
-  Altamente riciclabile  
Highly recyclable




**Intenso effetto uplight**  
**Design geometrico**  
**Ottica 10°**

Intense uplight effect  
Geometric design  
Optics 10°

## GEMMA Qd 35 IP67

	1W 350mA	2W 500mA	3W 350mA	Finiture Finish	Colore LED LED Colour
Lumen 3000K	100lm	150lm	300lm		
 10° Lens	730941._._-UL	730942._._-UL		3 Grigio - Gray 4 Nero - Black 6 Acciaio Inox Stainless Steel AISI 316L	U 2200K Y 2700K 6 3000K 9 4000K
 30° Lens	760941._._-UL	760942._._-UL			
 40° Lens	740941._._-UL	740942._._-UL			
 Vetro trasparente Transparent glass	720941._._-UL	720942._._-UL	720958._._-UL		
 Vetro satinato Frosted glass	710941._._-UL	710942._._-UL	710958._._-UL		
 Lente ellittica Elliptical lens	770941._._-UL	770942._._-UL			



ALIMENTATORI CONSIGLIATI (non inclusi)  
SUGGESTED DRIVERS (not included)

350mA **CC30-M-350-NW**  
500mA **CC30-M-500-NW**

ACCESSORI  
ACCESSORIES



Controcassa  
Recessed box  
**A00161.30**



Controcassa  
Recessed box  
**A00249.40**



Molle di fissaggio per Gemma Qd 35 IP67  
Spring mounting support for Gemma Qd 35 IP67  
**A00314.60**



EXAMPLE CODE COMPOSITION  
**123456.\_.\_-UL**

LED COLOUR  
FINISH