







DGA

# GEMMA Qd 35 IP67

## SOLOVETRO













-  IP67
-  Class III
-  Incasto a parete, pavimento  
Wall, floor recessed
-  WIPS - Water Infiltration Protection System
-  Carrabile 2000 kg  
Drive over up to 2000 kg
-  Installazione con controcassa obbligatoria  
Mandatory installation with recessed box
-  Cavo in neoprene 100 cm  
100 cm neoprene cable  
(disponibile lunghezza cavo su misura)  
(additional cable length available upon request)
-  Collegare in serie 350mA o 500mA  
Connect in series at 350mA or 500mA
-  100 gr
-  Altamente riciclabile  
Highly recyclable




**Elegante finitura in vetro**  
**Doppia possibilità di installazione**  
**Sistema antiabbagliamento**

Refined glassed surface  
Two different installation possibilities  
Low-glare system

### ■ GEMMA Qd 35 IP67 SOLOVETRO

	1W 350mA	2W 500mA	3W 350mA	Finiture Finish	Colore LED LED Colour
Lumen 3000K	100lm	150lm	300lm		
 10° Lens	733678._.-UL	733679._.-UL		 3 Grigio - Gray	 U 2200K
 30° Lens	763678._.-UL	763679._.-UL		 4 Nero - Black	 Y 2700K
 40° Lens	743678._.-UL	743679._.-UL		 Z Champagne Gold	 6 3000K
 Lente ellittica Elliptical lens	773678._.-UL	773679._.-UL			 9 4000K
 Vetro satinato Frosted glass	713678._.-UL	713679._.-UL	713680._.-UL		



ALIMENTATORI CONSIGLIATI (non inclusi)  
SUGGESTED DRIVERS (not included)

350mA CC30-M-350-NW  
500mA CC30-M-500-NW

ACCESSORI  
ACCESSORIES



Controcassa in alluminio con bordo  
Recessed box in aluminum with edge  
A00486.\_0



Controcassa materiale plastico con tappo  
Recessed box in plastic with closure cap  
A00481.40

FINISH  
Ø 38 mm

EXAMPLE CODE COMPOSITION  
123456.\_.-UL

LED COLOUR  
FINISH