

IN&OUT F



IP40



Class III



Incasso a parete, soffitto
Wall, ceiling recessed



Installazione a filo
Trimless installation



Collegare in serie 500mA o 700mA o 900mA
Connect in series at 500mA or 700mA or 900mA



360 gr



Ø 64 mm



Altamente riciclabile
Highly recyclable

IN&OUT F

Finiture
Finish

STRUTTURA
FRAME

A00654._ 0

Nell'ordine richiedere sempre
1 Struttura per ogni In&Out F
Please specify always 1 Frame for
each In&Out F in the purchase order

- 3 Grigio - Gray (with White finish)
- 4 Nero - Black (with Black finish or Dark Bronze finish)



MODULO - MODULE
IN&OUT F

3W 6W 9W
900mA 500mA 700mA

Lumen Output 3000K 250lm 500lm 650lm

Finiture
Finish

Colore LED
LED Colour

3° Lens	7T3927._ _		
10° Lens		733928._ _	733929._ _
30° Lens		763928._ _	763929._ _
50° Lens		7D3928._ _	7D3929._ _

- 7 Bianco - White
- B Bronzo Scuro
Dark Bronze
- H Nero - Black
- Y 2700K
- 6 3000K
- W 3000K CRI > 90
- J 3500K
- 9 4000K

MODULO - MODULE
IN&OUT F
CON NIDO D'APE
WITH HEX LOUVER

3W 6W 9W
900mA 500mA 700mA


Lumen Output 3000K 250lm 500lm 650lm

Finiture
Finish

Colore LED
LED Colour

3° Lens	7T3930._ _		
10° Lens		733931._ _	733932._ _
30° Lens		763931._ _	763932._ _
50° Lens		7D3931._ _	7D3932._ _

- 7 Bianco - White
- B Bronzo Scuro
Dark Bronze
- H Nero - Black
- Y 2700K
- 6 3000K
- W 3000K CRI > 90
- J 3500K
- 9 4000K



ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

500mA CC20-F-500-N
700mA CC20-F-700-N
900mA CC20-F-900-N

ACCESSORI
ACCESSORIES



Fresa a tazza
Hole saw
A00830.H0



Video installazione
Installation video
dga.it/it/prodotti/in-out-f.php

EXAMPLE CODE COMPOSITION
123456.

LED COLOUR
FINISH