

LIGHT SOURCE

LED quantity	1	
Power max	6 W – 8 W	
Total lumen output (3000K)	6W: 15° - 260 lm 40° - 258 lm	8W: 15° - 357 lm 40° - 354 lm
Efficacy lm/W (3000K)	6W: 15° - 44 lm/W 40° - 43 lm/W	8W: 15° - 45 lm/W 40° - 44 lm/W
UGR	12	
Ra	84	
LED Temperature	2700K – 3000K – 3000K CRI>90 – 4000K	
Average operational life	50.000 hours	

OPTIC

Material	PMMA
Available optics	15° - 40°
Beam direction	Adjustable: tilting +/-15°, rotating +/-360°
Flux symmetry	Symmetrical

FIXTURE

Material	Aluminum
Available finishes	Hard coat anodized: 3 - Gray 4 - Black Powder coated: 7 - White
IP Rate	IP40
Working Temperature	-20° ÷ +40°
Integrated fixing Systems	Springs

ELECTRICAL FEATURES



Driver	Remote
Dimmable	Push, 1-10V, DALI
Connection	In series at 180mA – 250mA
Class	III

MECHANICAL FEATURES


Dimensions (body)	Ø80 x 103 mm
Weight	290 gr
Installation	Wall, ceiling recessed
Cut-out	Ø73 mm
Use	Indoor

NOTES

Hex louver available as accessory upon request (A001162.40).



8W-15°



8W-40°