

# MIRUM Qm




-  IP40
-  Class III
-  Incasso a parete, soffitto  
Wall, ceiling recessed
-  Collegare in serie 180mA o 250mA o 350mA  
Connect in series at 180mA or 250mA or 350mA
-  425 gr
-  88x88 mm
-  Altamente riciclabile  
Highly recyclable



**Ideale per contesti residenziali**  
**Estetica minimale**  
**Quattro filtri ottici**


Ideal for residential settings  
Minimal aesthetics  
Four optical filters

## MIRUM Qm

STRUTTURA FRAME	A00874... 0				Finiture Finish	
	Nell'ordine richiedere 1 Struttura per ogni Modulo Mirum Q Please specify in the purchase order 1 Frame for each Mirum Q Modules				<input checked="" type="checkbox"/> H Nero - Black <input type="checkbox"/> 7 Bianco - White	
MODULO - MODULE MIRUM Q	6W 180mA	8W 250mA	12W 350mA	12W 350mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	500lm	650lm	900lm	1000lm (at source)		
 15° Reflector	7A4290..._	7A4291..._	7A4292..._		<input checked="" type="checkbox"/> H Nero - Black <input type="checkbox"/> 7 Bianco - White	<input checked="" type="checkbox"/> Y 2700K <input type="checkbox"/> 6 3000K <input type="checkbox"/> W 3000K CRI > 90 <input type="checkbox"/> 9 4000K <input type="checkbox"/> T 3000K CRI > 90 DIM-TO-WARM
 25° Reflector	7G4290..._	7G4291..._	7G4292..._			
 40° Reflector	744290..._	744291..._	744292..._	744293..._ T DIM-TO-WARM		







MIRUM Q



ALIMENTATORI CONSIGLIATI (non inclusi)  
SUGGESTED DRIVERS (not included)

180mA	CC20-F-180-N
250mA	CC9-F-250-N
350mA	CC20-F-350-N
350mA	CC20-A-350-N DIM-TO-WARM

ACCESSORI ACCESSORIES

			
Filtro Ellittico Linear Filter	Nido D'ape Hex Louver	Filtro Prismatico Prismatic Filter	Filtro Correttivo Softening Lens
IP40 A01164.80	A01162.40	A01165.80	A01163.80
Only for 15° reflector			

EXAMPLE CODE COMPOSITION  
123456

LED COLOUR
FINISH