








## MIRUM QFR

-  IP40
-  Class III
-  Incasso a parete, soffitto  
Wall, ceiling recessed
-  Installazione a filo  
Trimless installation
-  Collegare in serie 180mA o 250mA o 350mA  
Connect in series at 180mA or 250mA or 350mA
-  470 gr
-  90x90 mm
-  Altamente riciclabile  
Highly recyclable



**Orientabilità +/- 25°**  
**Dimensioni contenute**  
**Installazione a filo cartongesso**

Orientability +/- 25°  
 Small dimensions  
 Plasterboard flush installation

## ■ MIRUM QFR

STRUTTURA FRAME		A00410._ 0		Nell'ordine richiedere 1 Struttura per ogni Modulo Mirum QR Please specify in the purchase order 1 Frame for each Mirum QR Modules		<div><div><div></div><div>H</div></div><div><div></div><div>7</div></div></div> <div>Nero - Black Bianco - White</div>	
MODULO - MODULE MIRUM QR		6W 180mA	8W 250mA	12W 350mA	12W 350mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K		500lm	650lm	900lm	1000lm (at source)		
<div><div></div><div>15° Reflector</div></div>	7A4294._ _	7A4295._ _	7A4296._ _		<div><div><div></div><div>H</div></div><div><div></div><div>7</div></div></div> <div>Nero - Black Bianco - White</div>	<div><div></div><div>Y</div></div> <div>2700K</div>	
<div><div></div><div>25° Reflector</div></div>	7G4294._ _	7G4295._ _	7G4296._ _			<div><div></div><div>6</div></div> <div>3000K</div>	
						<div><div></div><div>W</div></div> <div>3000K CRI &gt; 90</div>	
						<div><div></div><div>9</div></div> <div>4000K</div>	
<div><div></div><div>40° Reflector</div></div>	744294._ _	744295._ _	744296._ _	744297. T		<div><div></div><div>T</div></div> <div>3000K CRI &gt; 90</div>	
				DIM-TO-WARM		DIM-TO-WARM	




+

MIRUM QR







+/- 355°



ALIMENTATORI CONSIGLIATI (non inclusi)  
 SUGGESTED DRIVERS (not included)

180mA	CC20-F-180-N
250mA	CC9-F-250-N
350mA	CC20-F-350-N
350mA	CC20-A-350-N DIM-TO-WARM

ACCESSORI  
 ACCESSORIES

				
	Filtro Ellittico Linear Filter	Nido D'ape Hex Louver	Filtro Prismatico Prismatic Filter	Filtro Correttivo Softening Lens
IP40	A01164.80	A01162.40	A01165.80	A01163.80
	Only for 15° reflector			

EXAMPLE CODE COMPOSITION  
 123456.

LED COLOUR  
 FINISH