








NEOS mR











-  IP40 / IP55
-  Class III
-  Incasso a parete, soffitto
Wall, ceiling recessed
-  Collegare in serie 300mA o 350mA
Connect in series at 300mA or 350mA
-  320 gr
-  Ø 92 mm
-  Altamente riciclabile
Highly recyclable




Spessore ridotto
Prestazioni di rilievo
Orientabilità +/- 25°











Small thickness
Outstanding performance
Orientability +/- 25°


NEOS mR IP40

	10W 300mA	12W 350mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	1200lm	1000lm at source		
 20° Lens	783781._._		<ul style="list-style-type: none">  H Nero - Black  7 Bianco - White 	<ul style="list-style-type: none">  Y 2700K  6 3000K  W 3000K CRI > 90  9 4000K  T 3000K CRI > 90 DIM-TO-WARM
 40° Reflector	723781._._	723963._.T <small>DIM-TO-WARM</small>		
 60° Reflector	753781._._	753963._.T <small>DIM-TO-WARM</small>		



NEOS mR IP55

	10W 300mA	12W 350mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	1200lm	1000lm at source		
 20° Lens	783782._._		<ul style="list-style-type: none">  H Nero - Black  7 Bianco - White 	<ul style="list-style-type: none">  Y 2700K  6 3000K  W 3000K CRI > 90  9 4000K  T 3000K CRI > 90 DIM-TO-WARM
 40° Reflector	723782._._	723964._.T <small>DIM-TO-WARM</small>		
 60° Reflector	753782._._	753964._.T <small>DIM-TO-WARM</small>		



ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

300mA CC20-F-300-N
350mA CC20-A-350-N

EXAMPLE CODE COMPOSITION

123456.

