

DGN

NESIS H65 Am











-  IP67
-  Class III
-  Incasso a parete, soffitto, pavimento
Wall, ceiling, floor recessed
-  WIPS - Water Infiltration Protection System
-  Carrabile 2000 kg
Drive over up to 2000 kg
-  Cavo in neoprene 100 cm
100 cm neoprene cable
(disponibile lunghezza cavo su misura)
(additional cable length available upon request)
-  Collegare in serie 350mA o 500mA
Connect in series at 350mA or 500mA
-  320 gr
-  Altamente riciclabile
Highly recyclable




Antiabbagliamento incluso
Design minimale

Anti-glare included
Minimal design

NESIS H65 Am

	3W 350mA	6W 500mA	Finiture Finish	Colore LED LED Colour
Lumen 3000K	300lm	450lm		
 10° Lens	733542._._-UL	733543._._-UL	 3 Grigio - Gray	 U 2200K
 30° Lens	763542._._-UL	763543._._-UL	 4 Nero - Black	 Y 2700K
 60° Lens	753542._._-UL	753543._._-UL	 6 Acciaio Inox Stainless Steel AISI 316L	 6 3000K
				 9 4000K



ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

350mA **CC30-M-350-NW**
500mA **CC30-M-500-NW**

ACCESSORI
ACCESSORIES



Controcassa
Recessed box
A00766.40



Controcassa
Recessed box
A00251.40



EXAMPLE CODE COMPOSITION
123456._._-UL

LED COLOUR
FINISH