





DGA


## TINI B 48V

-  IP40
-  Class III
-  Binario a parete, soffitto  
Wall, ceiling mounting track
-  Collegare a binario a bassa tensione 48Vdc  
Connect to 48Vdc low voltage track
-  90 gr
-  Altamente riciclabile  
Highly recyclable








## ■ TINI B 48V

	3W 48Vdc	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	300lm		
 15° Lens	7A4182._ _	<input type="checkbox"/> 7 Bianco - White	<input type="checkbox"/> U 2200K
 30° Lens	764182._ _	<input type="checkbox"/> B Bronzo Scuro Dark Bronze	<input type="checkbox"/> Y 2700K
 60° Lens	754182._ _	<input type="checkbox"/> H Nero - Black	<input type="checkbox"/> X 2700K CRI > 90
 Lente ellittica Elliptical lens	774182._ _		<input type="checkbox"/> 6 3000K
			<input type="checkbox"/> W 3000K CRI > 90
			<input type="checkbox"/> 9 4000K
			<input type="checkbox"/> 1 5000K



## ■ TINI B 48V DOUBLE

	3W x 2 48Vdc	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	2 x 300lm		
 15° Lens	7A4185._ _	<input type="checkbox"/> 7 Bianco - White	<input type="checkbox"/> U 2200K
 30° Lens	764185._ _	<input type="checkbox"/> B Bronzo Scuro Dark Bronze	<input type="checkbox"/> Y 2700K
 60° Lens	754185._ _	<input type="checkbox"/> H Nero - Black	<input type="checkbox"/> X 2700K CRI > 90
 Lente ellittica Elliptical lens	774185._ _		<input type="checkbox"/> 6 3000K
			<input type="checkbox"/> W 3000K CRI > 90
			<input type="checkbox"/> 9 4000K
			<input type="checkbox"/> 1 5000K



ALIMENTATORI CONSIGLIATI (non inclusi)  
SUGGESTED DRIVERS (not included)

48Vdc CV70-F-48-N pag. 617



Micro Binari 48Vdc  
48Vdc Micro Track

pag. 570

\* Prevedere 1 indirizzo DALI  
per ogni Tini B 48V / Tini B 48V Double  
Please consider 1 DALI address  
for each Tini B 48V / Tini B 48V Double

EXAMPLE CODE COMPOSITION  
123456.

LED COLOUR  
FINISH