

TONO mR













-  IP40 / IP55 disponibile su richiesta
available upon request
-  Class III
-  Incasso a parete, soffitto
Wall, ceiling recessed
-  Collegare in serie 500mA o 700mA o 900mA
Connect in series at 500mA or 700mA or 900mA
-  290 gr
-  Ø 73 mm
-  Altamente riciclabile
Highly recyclable




Quattro ottiche disponibili
Comfort luminoso
Dimensioni ridotte

Four optics available
Lighting comfort
Small size













■ TONO mR

	3W 900mA	6W 500mA	9W 700mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	250lm	500lm	650lm		
 3° Lens	7T3692._ _			 3 Grigio - Gray  4 Nero - Black  7 Bianco - White  Y 2700K  6 3000K  W 3000K CRI > 90  J 3500K  9 4000K	
 10° Lens		733691._ _	734025._ _		
 30° Lens		763691._ _	764025._ _		
 50° Lens		7D3691._ _	7D4025._ _		



■ TONO mR

CON NIDO D'APE - WITH HEX LOUVER

	3W 900mA	6W 500mA	9W 700mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	250lm	500lm	650lm		
 3° Lens	7T4283._ _			 3 Grigio - Gray  4 Nero - Black  7 Bianco - White  Y 2700K  6 3000K  W 3000K CRI > 90  J 3500K  9 4000K	
 10° Lens		734284._ _	734026._ _		
 30° Lens		764284._ _	764026._ _		
 50° Lens		7D4284._ _	7D4026._ _		

ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)







500mA	CC20-F-500-N
700mA	CC20-F-700-N
900mA	CC20-F-900-N

EXAMPLE CODE COMPOSITION

123456.



TONO mR IP55













-  IP55
-  Class III
-  Incasso a parete, soffitto
Wall, ceiling recessed
-  Collegare in serie 500mA o 700mA o 900mA
Connect in series at 500mA or 700mA or 900mA
-  290 gr
-  Ø 73 mm
-  Altamente riciclabile
Highly recyclable




Quattro ottiche disponibili
Comfort luminoso
Dimensioni ridotte

Four optics available
Lighting comfort
Small size













■ TONO mR IP55

	3W 900mA	6W 500mA	9W 700mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	250lm	500lm	650lm		
 3° Lens	7T4339._ _			<ul style="list-style-type: none"> <li style="width: 50%;"> 3 Grigio - Gray <li style="width: 50%;"> Y 2700K <li style="width: 50%;"> 4 Nero - Black <li style="width: 50%;"> 6 3000K <li style="width: 50%;"> 7 Bianco - White <li style="width: 50%;"> W 3000K CRI > 90 <li style="width: 50%;"> J 3500K <li style="width: 50%;"> 9 4000K 	
 10° Lens		734340._ _	734341._ _		
 30° Lens		764340._ _	764341._ _		
 50° Lens		7D4340._ _	7D4341._ _		



■ TONO mR IP55

CON NIDO D'APE - WITH HEX LOUVER

	3W 900mA	6W 500mA	9W 700mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	250lm	500lm	650lm		
 3° Lens	7T4342._ _			<ul style="list-style-type: none"> <li style="width: 50%;"> 3 Grigio - Gray <li style="width: 50%;"> Y 2700K <li style="width: 50%;"> 4 Nero - Black <li style="width: 50%;"> 6 3000K <li style="width: 50%;"> 7 Bianco - White <li style="width: 50%;"> W 3000K CRI > 90 <li style="width: 50%;"> J 3500K <li style="width: 50%;"> 9 4000K 	
 10° Lens		734343._ _	734344._ _		
 30° Lens		764343._ _	764344._ _		
 50° Lens		7D4343._ _	7D4344._ _		

ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

500mA	CC20-F-500-N
700mA	CC20-F-700-N
900mA	CC20-F-900-N

EXAMPLE CODE COMPOSITION

123456.

