

TONO P90

IP40

Class III

Montaggio a parete, soffitto, pavimento
Wall, ceiling, floor mounting

Collegare in serie 500mA o 700mA o 900mA
Connect in series at 500mA or 700mA or 900mA

180 gr

Altamente riciclabile
Highly recyclable




Massima orientabilità
Sistema antiabbagliamento
Quattro ottiche disponibili

Maximum orientability
Anti-glare system
Four optics available

TONO P90

	3W 900mA	6W 500mA	9W 700mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	250lm	500lm	650lm		
3° Lens	7T4045._ _			3 Grigio - Gray	Y 2700K
10° Lens		734046._ _	734047._ _	4 Nero - Black	6 3000K
30° Lens		764046._ _	764047._ _	T Titanio - Titanium	W 3000K CRI > 90
50° Lens		7D4046._ _	7D4047._ _	Z Champagne Gold	J 3500K
					9 4000K



TONO P90

CON NIDO D'APE - WITH HEX LOUVER

	3W 900mA	6W 500mA	9W 700mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	250lm	500lm	650lm		
3° Lens	7T4048._ _			3 Grigio - Gray	Y 2700K
10° Lens		734049._ _	734050._ _	4 Nero - Black	6 3000K
30° Lens		764049._ _	764050._ _	T Titanio - Titanium	W 3000K CRI > 90
50° Lens		7D4049._ _	7D4050._ _	Z Champagne Gold	J 3500K
					9 4000K

ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

500mA	CC20-F-500-N
700mA	CC20-F-700-N
900mA	CC20-F-900-N

EXAMPLE CODE COMPOSITION
123456.

