



TONO SUPER AF



IP40



Class III



Incasso a parete, soffitto
Wall, ceiling recessed



Installazione a filo
Trimless installation



Collegare in serie 500mA o 700mA o 900mA
Connect in series at 500mA or 700mA or 900mA



180 gr



Ø 50 mm



Altamente riciclabile
Highly recyclable


**Sorgente luminosa
antiabbagliamento
arretrata 70 mm**

70 mm low glare
recessed optic

STRUTTURA
FRAME

A00655.30

Nell'ordine richiedere sempre 1 Struttura per ogni Tono Super AF
Please specify always 1 Frame for each Tono Super AF in the purchase order



■ TONO SUPER AF IP40

	3W 900mA	6W 500mA	9W 700mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	250lm	500lm	650lm		
3° Lens	7T3936._ _			7 Bianco - White A Oro - Gold C Gothic Cement K Corten - Corten H Nero - Black L Bianco Perla Oyster White	Y 2700K 6 3000K W 3000K CRI > 90 J 3500K 9 4000K
10° Lens		733937._ _	733938._ _		
30° Lens		763937._ _	763938._ _		

ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

500mA CC20-F-500-N
700mA CC20-F-700-N
900mA CC20-F-900-N

ACCESSORI
ACCESSORIES



Fresa a tazza
Hole saw
A00832.H0



Video installazione
Installation video
dga.it/it/prodotti/tono-af.php

EXAMPLE CODE COMPOSITION
123456.

LED COLOUR
FINISH