

























# TRIUUM i IP67


-  IP67
-  Class III 24Vdc
-  Class II 220-240Vac
-  Incasso a pavimento  
Floor recessed
-  WIPS - Water Infiltration Protection System
-  Carrabile 2000 kg  
Drive over up to 2000 kg
-  Cavo in neoprene 100 cm  
100 cm neoprene cable  
(disponibile lunghezza cavo su misura)  
(additional cable length available upon request)
-  Collegare in parallelo 24Vdc  
Connect in parallel at 24Vdc
-  Alimentazione integrata, collegare alla tensione di rete 220-240Vac  
Built-in driver, connect directly to the line voltage to 220-240Vac
-  600 gr
-  Altamente riciclabile  
Highly recyclable



## TRIUUM i IP67














24Vdc


	7W 24Vdc	15W 24Vdc	Finitura flangia Bezel finish	Colore LED LED Colour	Filtri ottici Optical filters
Lumen Output 3000K	600lm	1000lm			
 10° Lens	734556. _ _ _	734570. _ _ _	 6S Acciaio Inox Satinato Brushed Stainless Steel AISI 316L	 U 2200K [1]	W Senza Filtro Without Filter
 25° Lens	7G4556. _ _ _	7G4570. _ _ _		 Y 2700K	D Frangiluce Louwer
 40° Lens	744556. _ _ _	744570. _ _ _		 6 3000K	F Frangiluce Asy Asy Louwer
 60° Lens	754556. _ _ _	754570. _ _ _		 W 3000K CRI > 90	
 Lente ellittica Elliptical lens	774556. _ _ _	774570. _ _ _		 J 3500K	
 Wall Washer	7W4556. _ _ W			 9 4000K	





## TRIUUM i IP67

220-240Vac

	8W 220-240Vac	Finitura flangia Bezel finish	Colore LED LED Colour	Filtri ottici Optical filters
Lumen Output 3000K	600lm			
 10° Lens	734576. _ _ _	 6S Acciaio Inox Satinato Brushed Stainless Steel AISI 316L	 U 2200K [1]	W Senza Filtro Without Filter
 25° Lens	7G4576. _ _ _		 Y 2700K	D Frangiluce Louwer
 40° Lens	744576. _ _ _		 6 3000K	F Frangiluce Asy Asy Louwer
 60° Lens	754576. _ _ _		 W 3000K CRI > 90	
 Lente ellittica Elliptical lens	774576. _ _ _		 J 3500K	
 Wall Washer	7W4576. _ _ W		 9 4000K	

ALIMENTATORI CONSIGLIATI (non inclusi)  
SUGGESTED DRIVERS (not included)

24Vdc CV20-F-24-N

ACCESSORI  
ACCESSORIESControcassa in acciaio  
Stainless Steel recessed box  
TRIUUM i IP67  
24V  
A01412.60Controcassa in acciaio  
Stainless Steel recessed box  
TRIUUM i IP67  
220-240Vac  
A01477.60Accessorio per  
estrazione  
Removing tool  
A01478.H0Micro connettore  
stagno  
Micro watertight  
connector  
A00357.40Connettore  
stagno  
Watertight  
connector  
A01023.40EXAMPLE CODE COMPOSITION  
123456.