











# ALIMENTATORI 500mA LED DRIVERS

USE WITH: 2W - 6W - 18W

## NON DIMMERABILI NON-DIMMABLE

IP20	CLASS 2 		nr. LED collegabili			
			Code	nr. of LEDs to connect	Vin	
IP20			CC6-F-500-S	min. 1 - max 3 LED 2W	100-240 Vac	Ø 36
IP20			CC20-F-500-N	min. 1 - max 10 LED 2W min. 1 - max 3 LED 6W min. 1 - max 1 LED 18W	220-240 Vac	Ø 55
			CC50-F-500-N	min. 1 - max 22 LED 2W min. 1 - max 5 LED 6W min. 1 - max 2 LED 18W	110-240 Vac	Ø 82

## DRIVERS IP67




IP67	CLASS 2 		nr. LED collegabili			
			Code	nr. of LEDs to connect	Vin	
IP67			CC20-F-500-PI	min. 1 - max 9 LED 2W min. 1 - max 2 LED 6W	220-240 Vac	Ø 47
			CC18-F-500-P	min. 1 - max 9 LED 2W min. 1 - max 2 LED 6W	90-264 Vac	Ø 45
			CC26-C-500-P	min. 1 - max 1 LED 18W min. 1 - max 4 LED 6W min. 4 - max 16 LED 2W	220-240 Vac	Ø 50

With box  
A00294.30  
page 216

Trailing Edge Dimming

Dimmerabile con taglio di fine fase.  
Trailing edge dimmable drivers.

## PER IMBARCAZIONI FOR BOATS







IP20	CLASS 2 		nr. LED collegabili			
			Code	nr. of LEDs to connect	Vin	
IP20			CC15-F-500-NB	min. 1 - max 3 LED 2W min. 1 - max 6 LED 2W	12 Vdc ≥ 24 Vdc	Ø 36

**DIMMERABILI**  
**DIMMABLE**


IP20




**CLASS 2**  
**RU US**



**CASAMBI**









**LOW Flicker**




**CLASS 2**  
**RU US**



**LOW Flicker**



**CASAMBI**



Vedi funzionamento dell'alimentatore dimmerabile multifunzione pag. 174  
See operation instructions of the multifunction dimmable driver page 174

Code	nr. LED collegabili nr. of LEDs to connect	Vin	
CC20-C-500-N	min. 5 - max 13 LED 2W min. 2 - max 3 LED 6W min. 1 - max 1 LED 18W	220-240 Vac	Ø 55
CC30-D-500-U	min. 1 - max 17 LED 2W min. 1 - max 4 LED 6W min. 1 - max 1 LED 18W	110-240 Vac	Ø 78
CC32-C-500-N	min. 1 - max 12 LED 2W min. 1 - max 3 LED 6W min. 1 - max 1 LED 18W	220-240 Vac	Ø 54
CC32-D-500-N	min. 2 - max 14 LED 2W min. 1 - max 4 LED 6W min. 1 - max 1 LED 18W	220-240 Vac	Ø 70
	min. 2 - max 10 LED 2W min. 1 - max 2 LED 6W	110-127 Vac	
CC32-M-500-N	min. 2 - max 14 LED 2W min. 1 - max 4 LED 6W min. 1 - max 1 LED 18W	220-240 Vac	Ø 70
	min. 2 - max 10 LED 2W min. 1 - max 2 LED 6W	110-127 Vac	
CC38-B-500-N	min. 1 - max 16 LED 2W min. 1 - max 4 LED 6W min. 1 - max 1 LED 18W	220-240 Vac	Ø 55
CC40-D-500-N	min. 8 - max 18 LED 2W min. 2 - max 4 LED 6W min. 1 - max 1 LED 18W	120-277 Vac	Ø 88
CC40-M-500-N	min. 5 - max 18 LED 2W min. 2 - max 4 LED 6W min. 1 - max 1 LED 18W	120-277 Vac	Ø 88
CC50-D-500-N	min. 1 - max 22 LED 2W min. 1 - max 5 LED 6W min. 1 - max 2 LED 18W	110-240 Vac	Ø 84
CC50-M-500-N	min. 1 - max 22 LED 2W min. 1 - max 5 LED 6W min. 1 - max 2 LED 18W	110-240 Vac	Ø 84
CC56-D-500-N	min. 5 - max 28 LED 2W min. 2 - max 7 LED 6W min. 1 - max 2 LED 18W	220-240 Vac	Ø 47
	min. 5 - max 26 LED 2W min. 2 - max 6 LED 6W min. 1 - max 2 LED 18W	110-127 Vac	
CC56-M-500-N	min. 5 - max 28 LED 2W min. 2 - max 7 LED 6W min. 1 - max 2 LED 18W	220-240 Vac	Ø 47
	min. 5 - max 26 LED 2W min. 2 - max 6 LED 6W min. 1 - max 2 LED 18W	110-127 Vac	
CC60-B-500-N	min. 1 - max 22 LED 2W min. 1 - max 5 LED 6W min. 1 - max 2 LED 18W	110-240 Vac	Ø 84

\* **POTENZIOMETRO**  
**POTENTIOMETER**



97000288



# ALIMENTATORI 900mA LED DRIVERS


USE WITH: 3W - 35W

## NON DIMMERABILI NON-DIMMABLE

 IP20

**CLASS 2**  




Code	nr. LED collegabili		
	nr. of LEDs to connect	Vin	
CC20-F-900-N	min. 1 - max 6 LED 3W	220-240 Vac	Ø 55
	min. 1 - max 4 LED 3W	110-127 Vac	
CC50-F-900-N	min. 1 - max 15 LED 3W min. 1 - max 1 LED 35W	220-240 Vac	Ø 82
	min. 1 - max 12 LED 3W min. 1 - max 1 LED 35W	110-127 Vac	

## DIMMERABILI DIMMABLE

 IP20

 Vedi funzionamento dell'alimentatore dimmerabile multifunzione pag. 174  
 See operation instructions of the multifunction dimmable driver page 174

Code	nr. LED collegabili		
	nr. of LEDs to connect	Vin	
CC20-D-900-NI	min. 1 - max 6 LED 3W	220-240 Vac	Ø 55
CC30-D-900-U	min. 1 - max 15 LED 3W	110-240 Vac	Ø 78
CC38-B-900-N CASAMBI MULTIFUNZIONE	min. 1 - max 12 LED 3W min. 1 - max 1 LED 35W	220-240 Vac	Ø 55
CC38-D-900-N DALI MULTIFUNZIONE	min. 6 - max 12 LED 3W min. 1 - max 1 LED 35W	220-240 Vac	Ø 55
CC50-D-900-N DALI MULTIFUNZIONE	min. 1 - max 19 LED 3W min. 1 - max 1 LED 35W	220-240 Vac	Ø 84
	min. 1 - max 12 LED 3W min. 1 - max 1 LED 35W	110-127 Vac	
CC50-M-900-NU	min. 1 - max 15 LED 3W min. 1 - max 1 LED 35W	110-240 Vac	Ø 78
CC50-D-900-U	min. 1 - max 15 LED 3W min. 1 - max 1 LED 35W	110-240 Vac	Ø 78
CC60-B-900-N CASAMBI MULTIFUNZIONE	min. 5 - max 18 LED 3W min. 1 - max 1 LED 35W	220-240 Vac	Ø 84
	min. 5 - max 12 LED 3W min. 1 - max 1 LED 35W	110-127 Vac	

