




## CROMA




-  IP40
-  Class III
-  Montaggio a parete, soffitto, pavimento  
Wall, ceiling, floor mounting
-  Collegare in serie 500mA  
Connect in series at 500mA
-  135 gr
-  Altamente riciclabile  
Highly recyclable




**Ottiche e snoot intercambiabili**  
**Alta efficienza**  
**Svariate tipologie di fissaggio**


Interchangeable optics and snoots  
High efficiency  
Various types of fastening

### CROMA

	6W 500mA	Finiture Finish	Colore LED LED Colour	Elementi di fissaggio Fixing element
Lumen Output 3000K	470lm			
 20° Lens	784355._ _ _	<ul style="list-style-type: none"> <li style="width: 50%;">■ 3 Grigio - Gray</li> <li style="width: 50%;">■ 6 3000K</li> <li style="width: 50%;">■ 4 Nero - Black</li> <li style="width: 50%;">■ 7 Bianco - White</li> <li style="width: 50%;">■ T Titanio - Titanium</li> <li style="width: 50%;">■ Z Champagne Gold</li> </ul>	<ul style="list-style-type: none"> <li style="width: 50%;">■ Y 2700K</li> <li style="width: 50%;">■ W 3000K CRI &gt; 90</li> <li style="width: 50%;">■ 9 4000K</li> <li style="width: 50%;">■ 1 5000K</li> </ul>	<ul style="list-style-type: none"> <li style="width: 50%;">G Ghiera - Ring nut</li> <li style="width: 50%;">M Magnetico - Magnetic</li> <li style="width: 50%;">P Applique - Applique</li> </ul>
 40° Lens	744355._ _ _			
 50° Lens	754355._ _ _			



Visiera cilindrica antiabbagliamento H 3 mm inclusa  
Low glare snoot H 3 mm included






VISIERA CILINDRICA ANTIABBLIAMENTO  
LOW GLARE SNOOT




VISIERA CILINDRICA ANTIABBLIAMENTO CON NIDO D'APE  
LOW GLARE SNOOT WITH HEX LOUVER



	VISIERA CILINDRICA ANTIABBLIAMENTO LOW GLARE SNOOT			VISIERA CILINDRICA ANTIABBLIAMENTO CON NIDO D'APE LOW GLARE SNOOT WITH HEX LOUVER		
	3 mm	10 mm	20 mm	3 mm	10 mm	20 mm
 20° Lens	A01000._0	A01006._0	A01012._0	A01001._0	A01007._0	A01013._0
 40° Lens	A01002._0	A01008._0	A01014._0	A01003._0	A01009._0	A01015._0
 50° Lens	A01004._0	A01010._0	A01016._0	A01005._0	A01011._0	A01017._0

FINISH




ALIMENTATORI CONSIGLIATI (non inclusi)  
SUGGESTED DRIVERS (not included)

500mA CC20-F-500-N

ELEMENTI DI FISSAGGIO  
FIXING ELEMENTS



Ghiera  
Ring nut  
G  
 Ø 10 mm

Magnetico  
Magnetic  
M

Applique  
Applique  
P

EXAMPLE CODE COMPOSITION  
123456.

