

## AURORA 1500 F



IP40



Class II



Binario a parete, soffitto  
Wall, ceiling mounting track



Fornito con attacco a filo per binario 230Vac  
Supplied with adaptor flush to 230Vac track



535 gr



Altamente riciclabile  
Highly recyclable




**Adattatore a filo per binario  
Alimentazione Integrata  
Elevato comfort visivo**

Flush to track adaptor  
Integrated Power Supply  
High visual comfort


### AURORA 1500 F

	21W 220-240Vac	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	1500lm		
15° Reflector	7A4201._ _	<input type="checkbox"/> 7 Bianco - White <input type="checkbox"/> H Nero - Black <input type="checkbox"/> W All White	<input type="checkbox"/> Y 2700K <input type="checkbox"/> 6 3000K <input type="checkbox"/> W 3000K CRI > 90 <input type="checkbox"/> 9 4000K
25° Reflector	7G4201._ _		
40° Reflector	744201._ _		



### AURORA 1500 F DALI

	21W 220-240Vac	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	1500lm		
15° Reflector	7A4202._ _	<input type="checkbox"/> 7 Bianco - White <input type="checkbox"/> H Nero - Black <input type="checkbox"/> W All White	<input type="checkbox"/> Y 2700K <input type="checkbox"/> 6 3000K <input type="checkbox"/> W 3000K CRI > 90 <input type="checkbox"/> 9 4000K
25° Reflector	7G4202._ _		
40° Reflector	744202._ _		



Binari 230Vac per Aurora F  
230Vac tracks for Aurora F

ACCESSORI  
ACCESSORIES



Nido D'ape  
Hex Louver  
A00732.40

EXAMPLE CODE COMPOSITION  
123456.

