























TRIUUM i IP67


-  IP67
-  Class III 24Vdc
-  Class II 220-240Vac
-  Incasso a pavimento
Floor recessed
-  WIPS - Water Infiltration Protection System
-  Carrabile 2000 kg
Drive over up to 2000 kg
-  Cavo in neoprene 100 cm
100 cm neoprene cable
(disponibile lunghezza cavo su misura)
(additional cable length available upon request)
-  Collegare in parallelo 24Vdc
Connect in parallel at 24Vdc
-  Alimentazione integrata, collegare alla tensione di rete 220-240Vac
Built-in driver, connect directly to the line voltage to 220-240Vac
-  600 gr
-  Altamente riciclabile
Highly recyclable



TRIUUM i IP67













24Vdc


	7W 24Vdc	15W 24Vdc	Finitura flangia Bezel finish	Colore LED LED Colour	Filtri ottici Optical filters
Lumen Output 3000K	600lm	1000lm			
 10° Lens	734556. _ _ _	734570. _ _ _	6S Acciaio Inox Satinato Brushed Stainless Steel AISI 316L	 U 2200K [1]  Y 2700K  6 3000K  W 3000K CRI > 90  J 3500K  9 4000K	W Senza Filtro Without Filter D Frangiluce Louwer F Frangiluce Asy Asy Louwer
 25° Lens	7G4556. _ _ _	7G4570. _ _ _			
 40° Lens	744556. _ _ _	744570. _ _ _			
 60° Lens	754556. _ _ _	754570. _ _ _			
 Lente ellittica Elliptical lens	774556. _ _ _	774570. _ _ _			[1] 2200K Disponibile solo per la versione 7W Available on the 7W power version only
 Wall Washer	7W4556. _ _ W				



TRIUUM i IP67

220-240Vac

	8W 220-240Vac	Finitura flangia Bezel finish	Colore LED LED Colour	Filtri ottici Optical filters
Lumen Output 3000K	600lm			
 10° Lens	734576. _ _ _	6S Acciaio Inox Satinato Brushed Stainless Steel AISI 316L	 U 2200K  Y 2700K  6 3000K  W 3000K CRI > 90  J 3500K  9 4000K	W Senza Filtro Without Filter D Frangiluce Louwer F Frangiluce Asy Asy Louwer
 25° Lens	7G4576. _ _ _			
 40° Lens	744576. _ _ _			
 60° Lens	754576. _ _ _			
 Lente ellittica Elliptical lens	774576. _ _ _			
 Wall Washer	7W4576. _ _ W			

ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

24Vdc CC20-F-24-N

ACCESSORI
ACCESSORIESControcassa in acciaio
Stainless Steel recessed box
TRIUUM i IP67
24V
A01412.60Controcassa in acciaio
Stainless Steel recessed box
TRIUUM i IP67
220-240Vac
A01477.60Accessorio per
estrazione
Removing tool
A01478.H0

24Vdc

Micro connettore
stagno
Micro watertight
connector
A00357.40

220-240Vac

Connettore
stagno
Watertight
connector
A01023.40EXAMPLE CODE COMPOSITION
123456.