






















GEMMA 35 IP67 SOLOVETRO

-  IP67
-  Class III
-  Incasso a parete, pavimento
Wall, floor recessed
-  WIPS - Water Infiltration Protection System
-  Carrabile 2000 kg
Drive over up to 2000 kg
-  Installazione con controcassa obbligatoria
Mandatory installation with recessed box
-  Cavo in neoprene 100 cm
100 cm neoprene cable
(disponibile lunghezza cavo su misura)
(additional cable length available upon request)
-  Collegare in serie 350mA o 500mA
Connect in series at 350mA or 500mA
-  90 gr
-  Altamente riciclabile
Highly recyclable



■ GEMMA 35 IP67 SOLOVETRO

	1W 350mA	2W 500mA	3W 350mA	Finiture Finish	Colore LED LED Colour
Lumen 3000K	100lm	150lm	300lm		
 10° Lens	733675._ _	733676._ _		 3 Grigio - Gray  4 Nero - Black  Z Champagne Gold	 U 2200K  Y 2700K  6 3000K  9 4000K
 30° Lens	763675._ _	763676._ _			
 40° Lens	743675._ _	743676._ _			
 Lente ellittica Elliptical lens	773675._ _	773676._ _			
 Vetro satinato Frosted glass	713675._ _	713676._ _	713677._ _		



ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

350mA CC20-F-350-N
500mA CC20-F-500-N

ACCESSORI
ACCESSORIES



Controcassa in alluminio con bordo
Recessed box in aluminum with edge
A00485._0



Controcassa materiale plastico con tappo
Recessed box in plastic with closure cap
A00480.40

FINISH
Ø 38 mm



Micro connettore stagno
Micro watertight connector
A00357.40

EXAMPLE CODE COMPOSITION
123456.

LED COLOUR
FINISH