









IRIDE 3 P IP68













-  IP68
-  Class III
-  Montaggio a parete, pavimento
Wall, floor mounting
-  WIPS - Water Infiltration Protection System
-  Cavo in neoprene 500 cm
500 cm neoprene cable
(disponibile lunghezza cavo su misura)
(additional cable length available upon request)
-  Collegare in serie 500mA
Connect in series at 500mA
-  2800 gr
-  Altamente riciclabile
Highly recyclable




Puntamento di precisione
Versione Dynamic White
Fascio largo e medio

Precision aiming
Dynamic White version
Wide and medium beam

IRIDE 3 P IP68

	 ALL WHITE 20W 500mA	 DYNAMIC WHITE 20W 500mA	 RGBW 20W 500mA	Finiture Finish	Colore LED LED Colour
 30° Lens	764122.6 _	764122.68	764122.67	 6 Acciaio Inox Stainless Steel AISI 316L	 Y 2700K  6 3000K  9 4000K  1 5000K  8 DYNAMIC WHITE  7 RGBW
 60° Lens	754122.6 _	754122.68	754122.67		



ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

- 500mA **CC32-D-500-N**
ALL WHITE
- CC52-D-500-NL**
DYNAMIC WHITE
- CC50-X-500-NL**
RGBW

ACCESSORI
ACCESSORIES



Connettore stagno
Wateright connector
A00387.40

EXAMPLE CODE COMPOSITION
123456

