

## LIGHT SOURCE

LED quantity	1
Power max	25W – 20W (dim-to-warm)
Total lumen output (3000K)	2439 lm (25W)
Efficacy lm/W (3000K)	98 lm/W (25W)
LOR (3000K)	70%
CRI	>80 – >90
LED Temperature (K)	2700 K – 3000 K – 3000K CRI>90 – 4000 K
Average operational life	50.000 hours

## OPTIC

Material	Glass reflector
Available optics	10°-20°-30°-40°
Beam direction	Adjustable +/-90°, Rotating +/-355°
Flux symmetry	Symmetrical
Accessories	-

## LED FIXTURE

Material	Aluminum
Finish	Painted (Black, White, All White)
Available finishes	Black, White, All White
IP Rate	IP40
Working Temperature	-20° ÷ +40°
Accessories	-



## ELECTRICAL FEATURES

Driver	Remote
Dimmable	Push, 1-10, DALI
For emergency lighting	Upon request
Connection in	In series at 600mA – 700mA
Class	III

## MECHANICAL FEATURES

Dimensions (mm)	Ø75 x 150 (cylinder only)
Weight	750 gr
Mounting	Wall, ceiling mounting
Cut-out (mm)	-
Use	Indoor

## NOTES



H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)
40°			
1.00	0.76	5195	3081
2.00	1.52	1299	770
3.00	2.28	577	342
4.00	3.04	325	193
5.00	3.80	208	123