

LIGHT SOURCE

LED quantity	1
Power max	18 W
Total lumen output (3000K)	713 lm (9°) – 860 lm (40°)
Efficacy lm/W (3000K)	40 lm/W (9°) – 48 lm/W (40°)
LOR (3000K)	45% (9°) - 54% (40°)
CRI	>80 - >90
LED Temperature (K)	2700 K – 3000 K – 3000K CRI>90 – 4000 K
Average operational life	50.000 hours

OPTIC

Material	Optical glass
Available optics	Zoom optic 9° - 40°
Beam direction	Adjustable +/- 90°, rotating +/- 355°
Flux symmetry	Symmetrical
Accessories	-

LED FIXTURE

Material	Aluminum
Finish	Painted (Black, White, All white)
Available finishes	Black, White, All white
IP Rate	IP40
Working Temperature	-20° ÷ +40°
Accessories	-



ELECTRICAL FEATURES

Driver	Built-in driver, provided with Eurostandard track connector
Dimmable	No
For emergency lighting	-
Connection in	In parallel at 220-240Vac
Class	II


MECHANICAL FEATURES

Dimensions (mm)	Ø61 x 140 (cylinder only)
Weight	750 gr
Mounting	Wall, ceiling mounting
Cut-out (mm)	-
Use	Indoor

NOTES



9°



40°