

MIRUM mR+



IP40 / IP55



Class III

Incasso a parete, soffitto
Wall, ceiling recessedCollegare in serie 180mA o 250mA o 350mA
Connect in series at 180mA or 250mA or 350mA

315 gr



Ø 78 mm


Altamente riciclabile
Highly recyclable

Alte performance
Massima flessibilità
Ampia scelta di ottiche

High performance
Maximum flexibility
Wide choice of optics


■ MIRUM mR+ IP40

	6W 180mA	8W 250mA	12W 350mA	12W 350mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	500lm	650lm	900lm	1000lm (at source)		
15° Reflector	7A4250._ _	7A4251._ _	7A4252._ _		□ 7 Bianco - White ■ H Nero - Black	□ Y 2700K □ 6 3000K □ W 3000K CRI > 90 □ 9 4000K □ T 3000K CRI > 90 DIM-TO-WARM
25° Reflector	7G4250._ _	7G4251._ _	7G4252._ _			
40° Reflector	744250._ _	744251._ _	744252._ _	744253._ T DIM-TO-WARM		



■ MIRUM mR+ IP55

	6W 180mA	8W 250mA	12W 350mA	12W 350mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	500lm	650lm	900lm	1000lm (at source)		
15° Reflector	7A4286._ _	7A4287._ _	7A4288._ _		□ 7 Bianco - White ■ H Nero - Black	□ Y 2700K □ 6 3000K □ W 3000K CRI > 90 □ 9 4000K □ T 3000K CRI > 90 DIM-TO-WARM
25° Reflector	7G4286._ _	7G4287._ _	7G4288._ _			
40° Reflector	744286._ _	744287._ _	744288._ _	744289._ T DIM-TO-WARM		



ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

180mA	CC20-F-180-N
250mA	CC9-F-250-N
350mA	CC20-F-350-N
350mA	CC20-A-350-N DIM-TO-WARM

ACCESSORI
ACCESSORIES

	Filtro Ellittico Linear Filter	Nido D'ape Hex Louver	Filtro Prismatico Prismatic Filter	Filtro Correttivo Softening Lens
IP40	A01164.80	A01162.40	A01165.80	A01163.80
IP55	A01168.80	A01166.40	A01169.80	A01167.80

Only for 15° reflector

EXAMPLE CODE COMPOSITION
123456.

LED COLOUR
FINISH