





MIRUM QF

-  IP40
-  Class III
-  Incasso a parete, soffitto
Wall, ceiling recessed
-  Installazione a filo
Trimless installation
-  Collegare in serie 180mA o 250mA o 350mA
Connect in series at 180mA or 250mA or 350mA
-  335 gr
-  80x80 mm
-  Altamente riciclabile
Highly recyclable



**Totale integrazione con
l'architettura**
Semplicità installativa
Due versioni disponibili


Full integration with architecture
Installation simplicity
Two versions available

■ MIRUM QF

STRUTTURA FRAME		Finiture Finish					
A00875._ 0		Nell'ordine richiedere 1 Struttura per ogni Modulo Mirum Q Please specify in the purchase order 1 Frame for each Mirum Q Modules					
MODULO - MODULE MIRUM Q	6W 180mA	8W 250mA	12W 350mA	12W 350mA	Finiture Finish	Colore LED LED Colour	
	Lumen Output 3000K	500lm	650lm	900lm		1000lm (at source)	
	15° Reflector	7A4290._ _	7A4291._ _	7A4292._ _			
	25° Reflector	7G4290._ _	7G4291._ _	7G4292._ _			
40° Reflector	744290._ _	744291._ _	744292._ _	744293._ T			
				DIM-TO-WARM			



MIRUM Q







89 - 6W
102 - 8W
113 - 12W

ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

180mA	CC20-F-180-N
250mA	CC9-F-250-N
350mA	CC20-F-350-N
350mA	CC20-A-350-N
	DIM-TO-WARM

ACCESSORI
ACCESSORIES

IP40				
	Filtro Ellittico Linear Filter	Nido D'aape Hex Louver	Filtro Prismatico Prismatic Filter	Filtro Correttivo Softening Lens
	A01164.80	A01162.40	A01165.80	A01163.80
	Only for 15° reflector			

EXAMPLE CODE COMPOSITION
123456.

LED COLOUR
FINISH