

## TONO Am

IP40 / IP55

Class III

Incasso a parete, soffitto  
Wall, ceiling recessed

Collegare in serie 500mA o 700mA o 900mA  
Connect in series at 500mA or 700mA or 900mA

150 gr

Ø 46 mm

Altamente riciclabile  
Highly recyclable




**Sorgente luminosa  
antiabbagliamento  
arretrata 30 mm**

30 mm low glare  
recessed optic

### TONO Am IP40

	3W 900mA	6W 500mA	9W 700mA	Finiture Finish (Painting)	Colore LED LED Colour
Lumen Output 3000K	250lm	500lm	650lm		
3° Lens	7T3764._ _			7 Bianco - White	Y 2700K
10° Lens		733765._ _	733766._ _	A Oro - Gold	6 3000K
30° Lens		763765._ _	763766._ _	C Gothic Cement	W 3000K CRI > 90
50° Lens		7D3765._ _	7D3766._ _	K Corten - Corten	J 3500K
				H Nero - Black	9 4000K
				L Bianco Perla Oyster White	



### TONO Am IP55

	3W 900mA	6W 500mA	9W 700mA	Finiture Finish (Painting)	Colore LED LED Colour
Lumen Output 3000K	250lm	500lm	650lm		
3° Lens	7T3802._ _			7 Bianco - White	Y 2700K
10° Lens		733803._ _	733804._ _	A Oro - Gold	6 3000K
30° Lens		763803._ _	763804._ _	C Gothic Cement	W 3000K CRI > 90
50° Lens		7D3803._ _	7D3804._ _	K Corten - Corten	J 3500K
				H Nero - Black	9 4000K
				L Bianco Perla Oyster White	

ALIMENTATORI CONSIGLIATI (non inclusi)  
SUGGESTED DRIVERS (not included)

500mA	CC20-F-500-N
700mA	CC20-F-700-N
900mA	CC20-F-900-N

EXAMPLE CODE COMPOSITION  
123456.

LED COLOUR
FINISH