

LIGHT SOURCE

LED quantity	1		
Power max	3 W – 6 W – 9 W		
Total lumen output (3000K)	3W: 3° - 174 lm	6W: 10° - 392 lm 30° - 314 lm 50° - 243 lm	9W: 10° - 488 lm 30° - 388 lm 50° - 247 lm
Efficacy lm/W (3000K)	3W: 3° - 58 lm/W	6W: 10° - 65 lm/W 30° - 52 lm/W 50° - 40 lm/W	9W: 10° - 54 lm/W 30° - 43 lm/W 50° - 27 lm/W
CRI	>80 – >90		
LED Temperature	2700K – 3000K – 3000K CRI>90 – 3500K - 4000K		
Average operational life	50.000 hours		

OPTIC

Material	PMMA
Available optics	3° - 10° - 30° - 50°
Beam direction	Fixed
Flux symmetry	Symmetrical

FIXTURE

Material	Aluminum, Stainless Steel
Available finishes	Hard coat anodized: 3 - Gray 4 - Black T - Titanium Powder coated: 7 - White As per material: 6 - Stainless steel AISI 316L
IP Rate	IP40, IP55
Working Temperature	-20° ÷ +40°
Integrated fixing Systems	-

ELECTRICAL FEATURES


Driver	Remote
Dimmable	Push, 1-10V, DALI
Connection	In series at 500mA – 700mA – 900mA
Class	III

MECHANICAL FEATURES





Dimensions	Ø47 x 93 mm
Weight	170 gr, 280 gr AISI 316L
Installation	Ceiling mounting
Cut-out	-
Use	Indoor

ACCESSORIES

Visors	-
Filters	-
Box/ Frame	-
Fixing system	-



PHOTOMETRIC DATA

3° Lens with hex louver – 3W	10° Lens with hex louver – 9W	30° Lens with hex louver – 9W	50° Lens with hex louver – 9W																																																																																																																
																																																																																																																			
<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td>3°</td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.08</td><td>14884</td><td>9110</td></tr> <tr> <td><u>2.00</u></td><td>0.15</td><td>3721</td><td>2278</td></tr> <tr> <td><u>3.00</u></td><td>0.23</td><td>1654</td><td>1012</td></tr> <tr> <td><u>4.00</u></td><td>0.30</td><td>930</td><td>569</td></tr> <tr> <td><u>5.00</u></td><td>0.38</td><td>595</td><td>364</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	3°				<u>1.00</u>	0.08	14884	9110	<u>2.00</u>	0.15	3721	2278	<u>3.00</u>	0.23	1654	1012	<u>4.00</u>	0.30	930	569	<u>5.00</u>	0.38	595	364	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td>10°</td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.17</td><td>9931</td><td>6086</td></tr> <tr> <td><u>2.00</u></td><td>0.35</td><td>2483</td><td>1521</td></tr> <tr> <td><u>3.00</u></td><td>0.52</td><td>1103</td><td>676</td></tr> <tr> <td><u>4.00</u></td><td>0.69</td><td>621</td><td>380</td></tr> <tr> <td><u>5.00</u></td><td>0.87</td><td>397</td><td>243</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	10°				<u>1.00</u>	0.17	9931	6086	<u>2.00</u>	0.35	2483	1521	<u>3.00</u>	0.52	1103	676	<u>4.00</u>	0.69	621	380	<u>5.00</u>	0.87	397	243	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td>30°</td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.40</td><td>2193</td><td>1354</td></tr> <tr> <td><u>2.00</u></td><td>0.80</td><td>548</td><td>339</td></tr> <tr> <td><u>3.00</u></td><td>1.20</td><td>244</td><td>150</td></tr> <tr> <td><u>4.00</u></td><td>1.60</td><td>137</td><td>85</td></tr> <tr> <td><u>5.00</u></td><td>2.00</td><td>88</td><td>54</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	30°				<u>1.00</u>	0.40	2193	1354	<u>2.00</u>	0.80	548	339	<u>3.00</u>	1.20	244	150	<u>4.00</u>	1.60	137	85	<u>5.00</u>	2.00	88	54	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td>50°</td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.59</td><td>797</td><td>482</td></tr> <tr> <td><u>2.00</u></td><td>1.17</td><td>199</td><td>120</td></tr> <tr> <td><u>3.00</u></td><td>1.76</td><td>89</td><td>54</td></tr> <tr> <td><u>4.00</u></td><td>2.34</td><td>50</td><td>30</td></tr> <tr> <td><u>5.00</u></td><td>2.93</td><td>32</td><td>19</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	50°				<u>1.00</u>	0.59	797	482	<u>2.00</u>	1.17	199	120	<u>3.00</u>	1.76	89	54	<u>4.00</u>	2.34	50	30	<u>5.00</u>	2.93	32	19
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																																																
3°																																																																																																																			
<u>1.00</u>	0.08	14884	9110																																																																																																																
<u>2.00</u>	0.15	3721	2278																																																																																																																
<u>3.00</u>	0.23	1654	1012																																																																																																																
<u>4.00</u>	0.30	930	569																																																																																																																
<u>5.00</u>	0.38	595	364																																																																																																																
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																																																
10°																																																																																																																			
<u>1.00</u>	0.17	9931	6086																																																																																																																
<u>2.00</u>	0.35	2483	1521																																																																																																																
<u>3.00</u>	0.52	1103	676																																																																																																																
<u>4.00</u>	0.69	621	380																																																																																																																
<u>5.00</u>	0.87	397	243																																																																																																																
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																																																
30°																																																																																																																			
<u>1.00</u>	0.40	2193	1354																																																																																																																
<u>2.00</u>	0.80	548	339																																																																																																																
<u>3.00</u>	1.20	244	150																																																																																																																
<u>4.00</u>	1.60	137	85																																																																																																																
<u>5.00</u>	2.00	88	54																																																																																																																
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																																																
50°																																																																																																																			
<u>1.00</u>	0.59	797	482																																																																																																																
<u>2.00</u>	1.17	199	120																																																																																																																
<u>3.00</u>	1.76	89	54																																																																																																																
<u>4.00</u>	2.34	50	30																																																																																																																
<u>5.00</u>	2.93	32	19																																																																																																																

NOTES