

LIGHT SOURCE

LED quantity	1		
Power max	3 W – 6 W – 9 W		
Total lumen output (3000K)	3W: 3° - 256 lm	6W: 10° - 493 lm 30° - 464 lm 50° - 381 lm	9W: 10° - 632 lm 30° - 574 lm 50° - 473 lm
Efficacy lm/W (3000K)	3W: 3° - 85 lm/W	6W: 10° - 82 lm/W 30° - 77 lm/W 50° - 63 lm/W	9W: 10° - 70 lm/W 30° - 64 lm/W 50° - 52 lm/W
CRI	>80 – >90		
LED Temperature	2700K – 3000K – 3000K CRI>90 – 3500K - 4000K		
Average operational life	50.000 hours		

OPTIC

Material	PMMA
Available optics	3° - 10° - 30° - 50°
Beam direction	Fixed
Flux symmetry	Symmetrical

FIXTURE

Material	Aluminum, Stainless Steel
Available finishes	Hard coat anodized: 3 - Gray 4 - Black T - Titanium Powder coated: 7 - White As per material: 6 - Stainless steel AISI 316L
IP Rate	IP40, IP55
Working Temperature	-20° ÷ +40°
Integrated fixing Systems	-

ELECTRICAL FEATURES


Driver	Remote
Dimmable	Push, 1-10V, DALI
Connection	In series at 500mA – 700mA – 900mA
Class	III

MECHANICAL FEATURES





Dimensions	Ø47 x 93 mm
Weight	170 gr, 280 gr AISI 316L
Installation	Ceiling mounting
Cut-out	-
Use	Indoor

ACCESSORIES

Visors	-
Filters	-
Box/ Frame	-
Fixing system	-



PHOTOMETRIC DATA

3° Lens – 3W	10° Lens – 9W	30° Lens – 9W	50° Lens – 9W																																																																																																																
																																																																																																																			
<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td>3°</td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.08</td><td>8057</td><td>4851</td></tr> <tr> <td><u>2.00</u></td><td>0.16</td><td>2014</td><td>1213</td></tr> <tr> <td><u>3.00</u></td><td>0.24</td><td>895</td><td>539</td></tr> <tr> <td><u>4.00</u></td><td>0.32</td><td>504</td><td>303</td></tr> <tr> <td><u>5.00</u></td><td>0.40</td><td>322</td><td>194</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	3°				<u>1.00</u>	0.08	8057	4851	<u>2.00</u>	0.16	2014	1213	<u>3.00</u>	0.24	895	539	<u>4.00</u>	0.32	504	303	<u>5.00</u>	0.40	322	194	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td>10°</td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.20</td><td>10422</td><td>6390</td></tr> <tr> <td><u>2.00</u></td><td>0.40</td><td>2606</td><td>1598</td></tr> <tr> <td><u>3.00</u></td><td>0.60</td><td>1158</td><td>710</td></tr> <tr> <td><u>4.00</u></td><td>0.80</td><td>651</td><td>399</td></tr> <tr> <td><u>5.00</u></td><td>1.00</td><td>417</td><td>256</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	10°				<u>1.00</u>	0.20	10422	6390	<u>2.00</u>	0.40	2606	1598	<u>3.00</u>	0.60	1158	710	<u>4.00</u>	0.80	651	399	<u>5.00</u>	1.00	417	256	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td>30°</td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.48</td><td>2327</td><td>1466</td></tr> <tr> <td><u>2.00</u></td><td>0.97</td><td>582</td><td>367</td></tr> <tr> <td><u>3.00</u></td><td>1.45</td><td>259</td><td>163</td></tr> <tr> <td><u>4.00</u></td><td>1.93</td><td>145</td><td>92</td></tr> <tr> <td><u>5.00</u></td><td>2.41</td><td>93</td><td>59</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	30°				<u>1.00</u>	0.48	2327	1466	<u>2.00</u>	0.97	582	367	<u>3.00</u>	1.45	259	163	<u>4.00</u>	1.93	145	92	<u>5.00</u>	2.41	93	59	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td>50°</td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.77</td><td>984</td><td>603</td></tr> <tr> <td><u>2.00</u></td><td>1.54</td><td>246</td><td>151</td></tr> <tr> <td><u>3.00</u></td><td>2.31</td><td>109</td><td>67</td></tr> <tr> <td><u>4.00</u></td><td>3.08</td><td>61</td><td>38</td></tr> <tr> <td><u>5.00</u></td><td>3.86</td><td>39</td><td>24</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	50°				<u>1.00</u>	0.77	984	603	<u>2.00</u>	1.54	246	151	<u>3.00</u>	2.31	109	67	<u>4.00</u>	3.08	61	38	<u>5.00</u>	3.86	39	24
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																																																
3°																																																																																																																			
<u>1.00</u>	0.08	8057	4851																																																																																																																
<u>2.00</u>	0.16	2014	1213																																																																																																																
<u>3.00</u>	0.24	895	539																																																																																																																
<u>4.00</u>	0.32	504	303																																																																																																																
<u>5.00</u>	0.40	322	194																																																																																																																
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																																																
10°																																																																																																																			
<u>1.00</u>	0.20	10422	6390																																																																																																																
<u>2.00</u>	0.40	2606	1598																																																																																																																
<u>3.00</u>	0.60	1158	710																																																																																																																
<u>4.00</u>	0.80	651	399																																																																																																																
<u>5.00</u>	1.00	417	256																																																																																																																
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																																																
30°																																																																																																																			
<u>1.00</u>	0.48	2327	1466																																																																																																																
<u>2.00</u>	0.97	582	367																																																																																																																
<u>3.00</u>	1.45	259	163																																																																																																																
<u>4.00</u>	1.93	145	92																																																																																																																
<u>5.00</u>	2.41	93	59																																																																																																																
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																																																
50°																																																																																																																			
<u>1.00</u>	0.77	984	603																																																																																																																
<u>2.00</u>	1.54	246	151																																																																																																																
<u>3.00</u>	2.31	109	67																																																																																																																
<u>4.00</u>	3.08	61	38																																																																																																																
<u>5.00</u>	3.86	39	24																																																																																																																

NOTES